

Products V165 to V172

V170 Stop watch, digital, non magnetic, having also watch functions. Precision 0.1 second.

V170-01 Stop watch, Mechanical dial type, non magnetic. Precision 0.1 second.

V171 Timing device From 0 to 60 minutes, with alarm



Soil Hydrometers

V172 Range 0.995 - 1.038 g/ml, div. 0.001 - 151 H

V172-02 Range -5 + 60 g/litre - 152 H

V172-03N Range 0.995 - 1.030 g/ml - BS 1377 - long stem

V172-04 Range 1.000 to 1.200 g/ml for additives

V172-05 Range 1200 to 1300 g/ml for aggregates. EN 1367-2



V166-01 Conductivity meter—thermometer

Digital, portable. Used for site and laboratory measurements of the conductivity in soils.

Measuring scale: 0 - 3999 uS/cm - resolution 1 uS/cm - accuracy 1%

Temperature in °C and °F., range 0 - 60 °C resolution 0.1 °C

Temperature calibration and compensation: automatic.

Use conditions: 0 to 50 °C, R.H. 100% Feeding: battery.

Weight: 100 g



V165 Termo-Hydrometer

Digital, portable, with detachable probe, it measures and displays in a short time both relative humidity and temperature.

Range: R.H. 20.0 to 95.0% - resolution 0.1% - accuracy ± 4% °C 0.0 to 60.0 - resolution 0.1 °C - accuracy ± 0.5%

Battery: 1x9 V

Dimensions: 185x82x45 mm

Weight: 400 g

